

1

Vulkan.

The Vulkan Sample Code Included with These Notes


Oregon State
University

Mike Bailey
mjb@cs.oregonstate.edu




This work is licensed under a [Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License](#)


Oregon State
University
Computer Graphics

SampleCode.pptx mjb – December 30, 2022

2

Sample Program Output




Oregon State
University
Computer Graphics

mjb – December 30, 2022

Sample Program Keyboard Inputs

3

'l' (ell), 'L':	Toggle l ighting off and on
'm', 'M':	Toggle display m ode (textures vs. colors, for now)
'p', 'P':	P ause the animation
'q', 'Q':	q uit the program
Esc:	quit the program
'r', 'R':	Toggle r otation-animation and using the mouse
'i', 'I':	Toggle using a vertex buffer only vs. an i ndex buffer (in the index buffer version)
'1', ...,'9','a',...'g'	Set the number of instances (in the instancing version)



Oregon State
University
Computer Graphics

mjb – December 30, 2022

Caveats on the Sample Code, I

4

1. I've written everything out in appalling longhand.
2. Everything is in one .cpp file (except the geometry data). It really should be broken up, but this way you can find everything easily.
3. At times, I could have hidden complexity, but I didn't. At all stages, I have tried to err on the side of showing you *everything*, so that nothing happens in a way that's kept a secret from you.
4. I've setup Vulkan structs every time they are used, even though, in many cases (most?), they could have been setup once and then re-used each time.
5. At times, I've setup things that didn't need to be setup just to show you what could go there.



Oregon State
University
Computer Graphics

mjb – December 30, 2022

Caveats on the Sample Code, II

5

6. There are great uses for C++ classes and methods here to hide some complexity, but I've not done that.
7. I've typedef'ed a couple things to make the Vulkan phraseology more consistent.
8. Even though it is not good software style, I have put persistent information in global variables, rather than a separate data structure
9. At times, I have copied lines from `vulkan_core.h` into the code as comments to show you what certain options could be.
10. I've divided functionality up into the pieces that make sense to me. Many other divisions are possible. Feel free to invent your own.



mjb – December 30, 2022

Main Program

6

```

int
main( int argc, char * argv[] )
{
    Width = 1024;
    Height = 1025;

    errno_t err = fopen_s( &FpDebug, DEBUGFILE, "w" );
    if( err != 0 )
    {
        fprintf( stderr, "Cannot open debug print file \"%s\n\", DEBUGFILE );
        FpDebug = stderr;
    }
    fprintf(FpDebug, "FpDebug: Width = %d ; Height = %d\n", Width, Height);

    Reset();
    InitGraphics();

    // loop until the user closes the window:

    while( glfwWindowShouldClose( MainWindow ) == 0 )
    {
        glfwPollEvents();
        Time = glfwGetTime();           // elapsed time, in double-precision seconds
        UpdateScene();
        RenderScene();
    }

    fprintf(FpDebug, "Closing the GLFW window\n");

    vkQueueWaitIdle( Queue );
    vkDeviceWaitIdle( LogicalDevice );
    DestroyAllVulkan();
    glfwDestroyWindow( MainWindow );
    glfwTerminate();
    return 0;
}

```



mjb – December 30, 2022

InitGraphics(), I

7

```

void
InitGraphics( )
{
    HERE_I_AM( "InitGraphics" );

    VkResult result = VK_SUCCESS;

    Init01Instance( );

    InitGLFW( );

    Init02CreateDebugCallbacks( );

    Init03PhysicalDeviceAndGetQueueFamilyProperties( );

    Init04LogicalDeviceAndQueue( );

    Init05UniformBuffer( sizeof(Matrices),      &MyMatrixUniformBuffer );
    Fill05DataBuffer( MyMatrixUniformBuffer, (void *) &Matrices );

    Init05UniformBuffer( sizeof(Light),       &MyLightUniformBuffer );
    Fill05DataBuffer( MyLightUniformBuffer, (void *) &Light );

    Init05MyVertexDataBuffer( sizeof(VertexData), &MyVertexDataBuffer );
    Fill05DataBuffer( MyVertexDataBuffer,         (void *) VertexData );

    Init06CommandPool( );
    Init06CommandBuffers( );

```



mjb - December 30, 2022

InitGraphics(), II

8

```

Init07TextureSampler( &MyPuppyTexture.texSampler );
Init07TextureBufferAndFillFromBmpFile("puppy.bmp", &MyPuppyTexture);

Init08Swapchain( );

Init09DepthStencilImage( );

Init10RenderPasses( );

Init11Framebuffers( );

Init12SpirvShader( "sample-vert.spv", &ShaderModuleVertex );
Init12SpirvShader( "sample-frag.spv", &ShaderModuleFragment );

Init13DescriptorSetPool( );
Init13DescriptorSetLayouts();
Init13DescriptorSets( );


Init14GraphicsVertexFragmentPipeline( ShaderModuleVertex, ShaderModuleFragment,
                                    VK_PRIMITIVE_TOPOLOGY_TRIANGLE_LIST, &GraphicsPipeline );
}

```



mjb - December 30, 2022

A Colored Cube



9

```
static GLfloat CubeVertices[ ][3] =
{
    { -1., -1., -1. },
    { 1., -1., -1. },
    { -1., 1., -1. },
    { 1., 1., -1. },
    { -1., -1., 1. },
    { 1., -1., 1. },
    { -1., 1., 1. },
    { 1., 1., 1. }
};
```

```
static GLfloat CubeColors[ ][3] =
{
    { 0., 0., 0. },
    { 1., 0., 0. },
    { 0., 1., 0. },
    { 1., 1., 0. },
    { 0., 0., 1. },
    { 1., 0., 1. },
    { 0., 1., 1. },
    { 1., 1., 1. }
};
```

```
static GLuint CubeTriangleIndices[ ][3] =
{
    { 0, 2, 3 },
    { 0, 3, 1 },
    { 4, 5, 7 },
    { 4, 7, 6 },
    { 1, 3, 7 },
    { 1, 7, 5 },
    { 0, 4, 6 },
    { 0, 6, 2 },
    { 2, 6, 7 },
    { 2, 7, 3 },
    { 0, 1, 5 },
    { 0, 5, 4 }
};
```






Oregon State
University
Computer Graphics

mjb – December 30, 2022


A Colored Cube



10

```
struct vertex
{
    glm::vec3 position;
    glm::vec3 normal;
    glm::vec3 color;
    glm::vec2 texCoord;
};

struct vertex VertexData[ ] =
{
    // triangle 0-2-3:
    // vertex #0:
    {
        { -1., -1., -1. },
        { 0., 0., -1. },
        { 0., 0., 0. },
        { 1., 0. }
    },
    // vertex #2:
    {
        { -1., 1., -1. },
        { 0., 0., -1. },
        { 0., 1., 0. },
        { 1., 1. }
    },
    // vertex #3:
    {
        { 1., 1., -1. },
        { 0., 0., -1. },
        { 1., 1., 0. },
        { 0., 1. }
    },
    ...
}
```





Computer Graphics

mjb – December 30, 2022

The Vertex Data is in a Separate File that is #include'd into sample.cpp

11

#include "SampleVertexData.cpp"

```
struct vertex
{
    glm::vec3    position;
    glm::vec3    normal;
    glm::vec3    color;
    glm::vec2    texCoord;
};

struct vertex VertexData[ ] =
{
    // triangle 0-2-3:
    // vertex #0:
    {
        { -1., -1., -1. },
        { 0., 0., -1. },
        { 0., 0., 0. },
        { 1., 0. }
    },
    // vertex #2:
    {
        { -1., 1., -1. },
        { 0., 0., -1. },
        { 0., 1., 0. },
        { 1., 1. }
    },
    ...
}
```



mjb – December 30, 2022

What if you don't need all of this information?

12

```
struct vertex
{
    glm::vec3    position;
    glm::vec3    normal;
    glm::vec3    color;
    glm::vec2    texCoord;
};
```

For example, what if you are not doing texturing in this application? Should you re-do this struct and leave the texCoord element out?

As best as I can tell, the only costs for retaining vertex attributes that you aren't going to use are some GPU memory space and possibly some inefficient uses of the cache, but not gross performance. So, I recommend keeping this struct intact, and, if you don't need texturing, simply don't use the texCoord values in your vertex or fragment shaders.



mjb – December 30, 2022

Vulkan Software Philosophy

13

Vulkan has lots of typedefs that define C/C++ structs and enums

Vulkan takes a non-C++ object-oriented approach in that those typedefed structs pass all the necessary information into a function. For example, where we might normally say using C++ class methods:

```
result = LogicalDevice->vkGetDeviceQueue ( queueFamilyIndex, queueIndex, OUT &Queue );
```

Vulkan has chosen to do it like this:

```
result = vkGetDeviceQueue ( LogicalDevice, queueFamilyIndex, queueIndex, OUT &Queue );
```



mjb – December 30, 2022

Vulkan Conventions

14

VkXxx is a typedef, probably a struct

vkYyy() is a function call

VK_ZZZ is a constant

My Conventions

“Init” in a function call name means that something is being setup that only needs to be setup once

The number after “Init” gives you the ordering

In the source code, after main() comes InitGraphics(), then all of the InitxxYYY() functions in numerical order. After that comes the helper functions

“Find” in a function call name means that something is being looked for

“Fill” in a function call name means that some data is being supplied to Vulkan

“IN” and “OUT” ahead of function call arguments are just there to let you know how an argument is going to be used by the function. Otherwise, IN and OUT have no significance. They are actually #define'd to nothing.

Computer Graphics

mjb – December 30, 2022

Querying the Number of Something and Allocating Enough Structures to Hold Them All

15

```

uint32_t count;
result = vkEnumeratePhysicalDevices( Instance, OUT &count, OUT (VkPhysicalDevice *)nullptr );

VkPhysicalDevice * physicalDevices = new VkPhysicalDevice[ count ];
result = vkEnumeratePhysicalDevices( Instance, OUT &count, OUT &physicalDevices[0] );

```

This way of querying information is a recurring OpenCL and Vulkan pattern (get used to it):

	How many total there are	Where to put them
result = vkEnumeratePhysicalDevices(Instance, &count, nullptr);		
result = vkEnumeratePhysicalDevices(Instance, &count, &physicalDevices[0]);		



mjb – December 30, 2022

Your Sample2019.zip File Contains This

16

Name	Date modified	Type	Size
vs	9/4/2019 2:34 PM	File folder	
Debug	9/4/2019 2:49 PM	File folder	
glm	9/4/2019 2:34 PM	File folder	
glm-0.9.8.5	9/4/2019 2:34 PM	File folder	
glm-0.9.9-a2	9/4/2019 2:34 PM	File folder	
ERRORS.ptx	6/29/2018 10:46 AM	Microsoft PowerP...	789 KB
frag.spv	1/10/2018 9:07 AM	SPV File	2 KB
glm.v3.h	12/26/2017 10:48 AM	C/C++ Header	149 KB
glfv3.lib	8/18/2016 5:06 AM	Object File Library	240 KB
glslangValidator	12/31/2017 5:24 PM	File	1,817 KB
glslangValidator.exe	6/15/2017 12:33 PM	Application	1,633 KB
glslangValidator.help	10/6/2017 2:31 PM	HELP File	6 KB
Makefile	1/31/2018 1:14:1 AM	File	1 KB
puppy.bmp	1/10/2018 8:13 AM	BMP File	3,073 KB
puppy.jpg	1/10/2018 8:13 AM	JPG File	443 KB
puppy0.bmp	1/1/2018 9:57 AM	BMP File	3,073 KB
puppy0.jpg	1/1/2018 9:58 AM	JPG File	455 KB
sample.cpp	9/4/2018 2:49 PM	C++ Source	138 KB
sample.shader.cpp	3/1/2018 12:46 PM	C++ Source	135 KB
Sample.sln	12/27/2017 9:45 AM	Microsoft Visual S...	2 KB
Sample.vcxproj	9/4/2019 2:37 PM	VC++ Project	7 KB
Sample.vcxproj.filters	12/27/2017 9:47 AM	VC++ Project File...	1 KB
Sample.vcxproj.user	6/29/2018 9:49 AM	Per-User Project O...	1 KB
sample0.pdf	1/9/2018 11:28 AM	Adobe Acrobat D...	84 KB
sample09.pdf	1/9/2018 11:28 AM	Adobe Acrobat D...	89 KB
sample10.pdf	1/9/2018 11:26 AM	Adobe Acrobat D...	94 KB
sample-comp.comp	2/14/2018 12:25 PM	COMP File	2 KB
sample-comp.spv	2/14/2018 12:25 PM	SPV File	4 KB
sample-frag.frag	2/18/2018 10:52 AM	FRAG File	2 KB

The "19" refers to the version of Visual Studio, not the year of development.

mjb – December 30, 2022

Reporting Error Results, I

17

```

struct errorcode
{
    VkResult resultCode;
    std::string meaning;
}
ErrorCodes[ ] =
{
    { VK_NOT_READY, "Not Ready" },
    { VK_TIMEOUT, "Timeout" },
    { VK_EVENT_SET, "Event Set" },
    { VK_EVENT_RESET, "Event Reset" },
    { VK_INCOMPLETE, "Incomplete" },
    { VK_ERROR_OUT_OF_HOST_MEMORY, "Out of Host Memory" },
    { VK_ERROR_OUT_OF_DEVICE_MEMORY, "Out of Device Memory" },
    { VK_ERROR_INITIALIZATION_FAILED, "Initialization Failed" },
    { VK_ERROR_DEVICE_LOST, "Device Lost" },
    { VK_ERROR_MEMORY_MAP_FAILED, "Memory Map Failed" },
    { VK_ERROR_LAYER_NOT_PRESENT, "Layer Not Present" },
    { VK_ERROR_EXTENSION_NOT_PRESENT, "Extension Not Present" },
    { VK_ERROR_FEATURE_NOT_PRESENT, "Feature Not Present" },
    { VK_ERROR_INCOMPATIBLE_DRIVER, "Incompatible Driver" },
    { VK_ERROR_TOO_MANY_OBJECTS, "Too Many Objects" },
    { VK_ERROR_FORMAT_NOT_SUPPORTED, "Format Not Supported" },
    { VK_ERROR_FRAGMENTED_POOL, "Fragmented Pool" },
    { VK_ERROR_SURFACE_LOST_KHR, "Surface Lost" },
    { VK_ERROR_NATIVE_WINDOW_IN_USE_KHR, "Native Window in Use" },
    { VK_SUBOPTIMAL_KHR, "Suboptimal" },
    { VK_ERROR_OUT_OF_DATE_KHR, "Error Out of Date" },
    { VK_ERROR_INCOMPATIBLE_DISPLAY_KHR, "Incompatible Display" },
    { VK_ERROR_VALIDATION_FAILED_EXT, "Validation Failed" },
    { VK_ERROR_INVALID_SHADER_NV, "Invalid Shader" },
    { VK_ERROR_OUT_OF_POOL_MEMORY_KHR, "Out of Pool Memory" },
    { VK_ERROR_INVALID_EXTERNAL_HANDLE, "Invalid External Handle" }
};

```



mjb - December 30, 2022

Reporting Error Results, II

18

```

void
PrintVkError( VkResult result, std::string prefix )
{
    if (Verbose && result == VK_SUCCESS)
    {
        fprintf(FpDebug, "%s: %s\n", prefix.c_str(), "Successful");
        fflush(FpDebug);
        return;
    }

    const int numErrorCodes = sizeof( ErrorCodes ) / sizeof( struct errorcode );
    std::string meaning = "";
    for( int i = 0; i < numErrorCodes; i++ )
    {
        if( result == ErrorCodes[i].resultCode )
        {
            meaning = ErrorCodes[i].meaning;
            break;
        }
    }

    fprintf( FpDebug, "\n%s: %s\n", prefix.c_str(), meaning.c_str() );
    fflush(FpDebug);
}

```

Oregon State
University
Computer Graphics

mjb - December 30, 2022

Extras in the Code

19

```
#define REPORT(s)      { PrintVkError( result, s ); fflush(FpDebug); }

#define HERE_I_AM(s)    if( Verbose ) { fprintf( FpDebug, "***** %s *****\n", s ); fflush(FpDebug); }

bool        Paused;

bool        Verbose;

#define DEBUGFILE       "VulkanDebug.txt"
errno_t err = fopen_s( &FpDebug, DEBUGFILE, "w" );

const int32_t  OFFSET_ZERO = 0;
```



mjb – December 30, 2022